

IN THE CLAIMS

Please amend claims 1-3, 5-6, 9-10, 12, 18, and 20-24 as indicated below.

Sub C1
1. (Currently Amended)

An apparatus, comprising:

~~a first storage to store a plurality of data, said first storage coupled to a host bus through a first path and responsive to one or more of a plurality of control signals to transfer selected parts of said data to said host bus; and~~
an interface for directly coupling to a host bus having one or more processors;
a device coupled to the interface to perform one or more functions, said device appearing as a virtual PCI device logically residing on a PCI bus that is coupled to the host bus through a host-to-PCI bridge; and
a monitor circuit; coupled to said interface and said device ~~host bus~~ to track ~~processor~~ initiated host bus cycles initiated by at least one of the processors coupled to the host bus, and to identify processor initiated host bus read cycles targeted to the virtual PCI device, and a virtual PCI device logically residing behind a primary PCI bus, wherein said primary PCI bus is coupled to said host bus through a second path which is distinct from said first path;
~~wherein said monitor circuit is to generate said plurality of~~ one or more control signals to enable the device to respond, as the virtual PCI device, to said transfer a select one or more said data to said host bus during one or more of said identified host bus read cycles targeted to said virtual PCI device.

2. (Currently Amended)

The apparatus of claim 1, ~~wherein said virtual PCI device is a virtual PCI-PCI bridge~~ further comprising a first storage coupled to the interface and the

monitor circuit to store data associated with host bus read cycles addressed to the virtual PCI device, wherein the data is transferred from the first storage to the host bus during the host bus read cycles.

3. (Currently Amended) The apparatus of claim 2 ~~1~~, further comprising a second storage coupled to ~~said host bus and responsive to one or more of said plurality of control signals to selectively receive said data from said host bus to store in said second storage;~~

~~wherein said virtual PCI device resides logically behind a virtual PCI-to-PCI bridge which resides logically behind said primary PCI bus; and~~

to the interface and the monitor circuit to store data associated with host bus write cycles addressed to the virtual PCI device, wherein the data is transferred from the host bus to the second storage during the host bus write cycles

~~wherein said monitor circuit is to further identify host bus write cycles targeted to a location, within a configuration space reserved for said virtual PCI-to-PCI bridge, which specifies a bus number and to generate said control signals to receive said bus number from said host bus to store in said second storage.~~

4. (Original) The apparatus of claim 1, further comprising a processor which is coupled to said host bus, wherein said processor, said first storage, and said monitor circuit are integrated into a single chip package.

5. (Currently Amended) The apparatus of claim 3, ~~wherein said first storage and said monitor circuit are coupled to said host bus through~~ further comprising an internal processor bus to connect the device, the monitor circuit, and the first and second storages to the interface.

6. (Currently Amended) The apparatus of claim 1, wherein ~~said first storage is responsive to one or more of said plurality of control signals to selectively receive data from said host bus to store in said first storage;~~

~~wherein said monitor circuit is to further identify processor initiated host bus write cycles targeted to said virtual PCI device residing logically behind said primary PCI bus;~~

~~wherein said monitor circuit is to generate said plurality of control signals to receive data from said host bus to store in said storage during one or more of said identified host bus write cycles targeted to said virtual PCI device~~

the device is a bridge device coupled to one or more other devices and the device appears as a virtual PCI-PCI bridge logically residing on a PCI bus coupling to a host-to-PCI bridge.

7. (Original) The apparatus of claim 1, wherein said storage is comprised of random access memory; and said identified host bus read cycles targeted to said virtual PCI device include host bus cycles targeted to memory address space allocated to said virtual PCI device.

8. (Original) The apparatus of claim 1, further comprising a mirror register coupled to said host bus and responsive to one or more of said control signals to receive data from said host bus;

wherein said monitor circuit is to further identify host bus write cycles targeted to a configuration-address register; and

wherein said monitor circuit is to generate said control signals to receive data from said host bus to store in said mirror register during said host bus cycles identified as targeted to said configuration-address register.

9. (Currently Amended) The apparatus of claim 1, wherein said identified host bus read cycles targeted to said virtual PCI device include host bus cycles to I/O address space allocated to said virtual PCI device.

10. (Currently Amended) The apparatus of claim 2, wherein said first storage includes a first plurality of configuration registers; and

wherein said identified host bus cycles include host bus cycles targeted to configuration space reserved for said virtual PCI device.

11. (Original) The apparatus of claim 10, wherein said virtual PCI device resides behind a virtual PCI-to-PCI bridge, and

wherein said first storage includes a second plurality of configuration registers, and wherein said monitor circuit is to further identify host bus cycles targeted to configuration space allocated to said virtual PCI-to-PCI bridge, and

wherein said monitor circuit is to generate said plurality of control signals to transfer a select one or more said data to said host bus during one or more of said identified host bus read cycles targeted to said configuration space allocated to said virtual PCI-to-PCI bridge.

12. (Currently Amended) An apparatus, comprising:
an interface for directly coupling to a host bus;

a first storage, wherein contents of said first storage specify a first address space allocated to a primary PCI bus; -

a device coupled to the interface to perform one or more functions, the device appearing as a virtual PCI device logically residing on a PCI bus coupled to the primary PCI bus;

a second storage, wherein contents of said second storage specify a second address space allocated to a said virtual PCI device ~~logically residing behind said primary PCI bus;~~ and

a control circuit, coupled to said first and said second storage, wherein said control circuit is to couple to a host bus to track processor initiated host bus cycles and to select host bus cycles to route to said primary PCI bus, wherein said routed cycles are to be selected, based on said contents of said first storage and said second storage, to exclude host bus cycles targeted to said second address space.

13. (Original) The apparatus of claim 12, wherein said first and said second address space includes memory host bus address space.

14. (Original) The apparatus of claim 12, wherein said first and said second address space includes host bus I/O space.

15. (Original) The apparatus of claim 12, wherein said first and said second address space includes PCI compliant configuration address space.

16. (Original) The apparatus of claim 12, wherein said virtual PCI device is a virtual PCI-to-PCI bridge.

17. (Original) The apparatus of claim 16, further comprising:

a plurality of configuration registers;

a third storage coupled to said control circuit, wherein contents of said third storage

indicate a bus and a device number in which said virtual PCI-to-PCI bridge

logically resides, and wherein said control circuit is to further select, based on

said bus and said device number, host bus cycles, targeted to configuration

address space of said virtual PCI-to-PCI bridge, to route to said plurality of

configuration registers.

18. (Currently Amended) A system comprising:

one or more processors coupled to a host bus;

a host-to-PCI bridge coupling a primary PCI bus to the host bus, said host-to-PCI

bridge to route select processor initiated host bus cycles to a the primary PCI

bus; and

a first host bus device; coupled to said host bus and appearing as a first virtual PCI

device logically residing on a PCI bus coupled to the primary PCI bus, to

monitor said host bus, to identify processor initiated host bus cycles targeted

to a said first virtual PCI device which resides logically behind said primary

PCI bus, and to intercept select said identified cycles targeted to said first

virtual PCI device;

wherein said host-to-PCI bridge is to not forward said identified cycles which are targeted to said first virtual PCI device.

19. (Original) The system of claim 18, wherein said first host bus device includes a plurality of configuration registers, wherein said intercepted cycles, include host bus cycles targeted to configuration space reserved for said first virtual PCI device and are to be routed to access said plurality of configuration registers.

20. (Currently Amended) The system of claim 18, wherein said first host bus device includes an array of memory devices, wherein said intercepted cycles include host bus cycles targeted to a memory space allocated to said first virtual PCI device and are to be routed to access said array of memory devices.

21. (Currently Amended) The system of claim 18, further comprising ~~comprised of~~ a second host bus device coupled to said host bus, the second host bus device appearing as a second virtual PCI device logically residing on a PCI bus coupled to the primary PCI bus, and the first and second virtual PCI devices having a unique combination of a PCI bus number and device number ~~wherein each said host bus device intercepts host bus cycles targeted to a distinct virtual PCI device which resides logically behind said primary PCI bus, wherein said distinct virtual PCI devices each have a distinct bus number and device number combination.~~

22. (Currently Amended) The system of claim 18, wherein said first virtual PCI device resides logically behind a primary virtual PCI-to PCI bridge, wherein said primary virtual PCI-to-PCI bridge resides logically behind said primary PCI bus, and wherein said first host

bus device is to snoop said host bus to determine a bus number assigned to said primary virtual PCI-to PCI bus.

23. (Currently Amended) The system of claim 22, wherein said first virtual PCI device resides logically behind a secondary virtual PCI-to PCI bridge which resides logically behind said primary virtual PCI-to-PCI bridge; ~~and,~~

wherein said first host bus device includes a plurality of bridge configuration registers, and wherein said intercepted cycles include host bus cycles targeted to the configuration space reserved for said secondary virtual PCI-to PCI bridge and are to be routed to access said plurality of bridge configuration registers.

24. (Currently Amended) A method comprising:

capturing a current host bus cycle initiated by a processor coupled to a host bus;

determining whether said captured cycle is targeted to a virtual PCI device residing

logically at a PCI bus behind a primary PCI bus, the virtual PCI device

representing a host bus device directly coupled to the host bus; and

intercepting said current host bus cycle, if said current cycle is determined to be

targeted to said virtual PCI device, and not routing said cycle to said primary

PCI bus.

25. (Original) The method of claim 24, wherein said intercepting includes routing to access a storage coupled to said host bus.

26. (Original) The method of claim 24, wherein said intercepting includes routing to access a location within a plurality of configuration registers.

27. (Original) The method of claim 24, wherein said determining includes determining whether said current cycle is a write cycle targeted to a configuration-address register and snooping said current host bus cycle to receive data from said host bus if said current cycle is a write cycle targeted to said configuration-address register and writing some or all of said data into a mirror register.

28. (Original) The methods of claim 24, wherein said determining includes determining whether said current cycle is a write cycle targeted to a location within the configuration registers of a virtual primary PCI-to-PCI bridge in which a bus number is specified; and snooping said current host bus cycle to receive data from said host bus if the current cycle is a write cycle to a location within the configuration registers of a virtual primary PCI-to-PCI bridge in which a bus number is specified and writing said data in a storage.

29. (Original) The method of claim 24, wherein said determining includes determining whether said cycle is to a location within the configuration registers of a virtual PCI-to-PCI bridge; and intercepting said current host bus to route to access a location within a plurality of bridge configuration registers if said cycle is to a location within the configuration registers of a virtual PCI-to-PCI bridge.

30. (Original) The method of claim 24 wherein said virtual PCI device is a virtual PCI-to-PCI bridge.